

## WALL MAJESTY ACRYLIC DISTEMPER

Titan Paints WALL MAJESTY ACRYLIC DISTEMPER is Water based paint specially made for Interior walls which provide the smoother finish.

### PRODUCT BENEFITS

1. It provides smooth and matt finish
2. This product has excellent stain Resistance, by which water base stains like tea, coffee can be easily removed
3. Acrylic Interior Emulsion conforms the low VOC and absence of any harmful chemical
4. Good intercoat adhesion to prevent from peel off
5. It prevents from growth of algae and Fungus on interior walls
6. Excellent Washability

### PRODUCT FEATURES

- |                          |                                                                                  |
|--------------------------|----------------------------------------------------------------------------------|
| 1. Coverage              | 85-100 sq-ft (2 Coat)*                                                           |
| 2. Drying Time           | 30 Min(SD), 4 Hrs (HD)                                                           |
| 3. Recommendation finish | Interior Cement Plasters, Interior Ceilings, Existing water base Paint Surfaces. |

\*Actual coverage may vary depends on the concrete surface, surface porosity & roughness, application method.

### TECHNICAL DATA

1. RECOMMENDED THINNER/Mixing media	WATER
2. GLOSS/SHEEN	MATT
3. METHOD OF APPLICATION	SRPAY/BRUSH/ROLLER
4. MIXING RATIO	2:1 by VOL/ AS PER REQUIRED CONSISTENCY

6. FLASH POINT	NON FLAMMABLE
7. STABILITY OF THINNED PAINT	RECOMMENDED TO USE WITHIN 24 HRS
5. NO. OF COATS	1 (IF REQUIRED APPLY 1 MORE FOR BETTER FINISH)
9. SAFETY DATA	Refer MSDS

# TECHNICAL DATA SHEET

## Paint Application Process

Application	Thinner	Dilution % (By Volume)	Recoating Period
STEP 1 Titan Wall Putty (Optional)	Water	As per requirement to form paste	4 Hrs
STEP 2 Interior Wall Primer (Brush/Roller/Spray)	Water	Brush 1:1 Roller 1:1 Spray 1:0.5	4 Hrs
STEP 3 First Coat Wall Majesty Acrylic Distemper (Brush/Roller/Spray)	Water	Brush 1:1 Roller 1:1 Spray 1:0.5	3-4 Hrs
STEP 4 Second Coat Wall Majesty Acrylic Distemper (Brush/Roller/Spray)	Water	Brush 1:1 Roller 1:1 Spray 1:0.5	3-4 Hrs


## Precautions

1. Do not apply at low temperature less than 10<sup>0</sup>C.
2. Do not use any colorants in primer
3. Stir well before use
4. Do not over thin
5. Keep the Container Closed when it not in use to prevent drying.
6. Prevent to contact with eyes and keep away from Children.

## Safety Points

1. Please refer the MSDS of Wall Majesty Acrylic distemper for handling and end use of Paint.
2. Do not pour leftover paint down the drain or in water sources.
3. Safety Data Sheet available on request.
4. In case of skin contact immediately wash skin with soap and plenty of water.
5. Always use mask, eye protection during application of Paint, In case of contact with eyes, rinse immediately with plenty of water and proceed for medical advice.

### Available Pack Sizes



Shelf Life: Shelf life for this product is 2 years from date of manufacturing when it enclosed in original tightly closed containers and away from direct sunlight & excessive heat

Version No. TPCL01/10/2019

Please note That this datasheet Supersedes all previous versions

For Feedback/Complaints, write to us at

**Titan Paints and Chemicals (P)Limited**

Door No. 305, Pollachi Main road, Sundarapuram, Coimbatore (TN) -641021

Email ( ) : [dpdsales@titanpaints.in](mailto:dpdsales@titanpaints.in)

Phone ( ) : 0422-2672894